

WOODSAFE®

2.19 Declaration of Performance Woodsafe WFX Heat modified Poplar panel Saicos oil

<i>Document name</i> 2.19 Declaration of Performance Woodsafe WFX Heat modified Poplar panel Saicos oil	<i>Governing document</i> CPR305/2011, EN14915:2013 0402-CPR-SC0260-15	<i>Language / Språk</i> English	<i>Number of pages DoP</i> 3
<i>Fire impregnation system</i> WOODSAFE® Exterior WFX™	<i>Description</i> Waterproof (polymeric) fire impregnation for wooden panels	<i>Version</i> 2	<i>Product code</i> 19
<i>Compiled by</i> Peter Johnson, CPO peter.johnson@woodsafes.com		<i>Supersedes version</i> 1	
<i>Approved by</i> Thomas Bengtsson, CEO thomas.bengtsson@woodsafes.com.		<i>Date</i> 2025-02-18	

1. Product group

WOODSAFE® WFX Heat modified Poplar panel Saicos oil, in thickness min 18(9)mm.

2. Construction product identification

Fire protection system: WOODSAFE® Exterior WFX, fire impregnation
Wood treatment: Heat modified
Wood specie and product type: Poplar panel
Surface treatment: Saicos oil H9660, 2 x 70 g/m² (wet)
Product code: 19

Sawn, planed and profiled wooden panels installed with an opening that meet the requirements according to EN14915:2013. Fire protection impregnated according to system Woodsafe Exterior WFX. For more information, see page 2 of this Declaration of performance as well as package specification and associated document.

3. The products intended end use/uses

Exterior wooden panel as cladding with material properties against fire.

4. Manufacturer

Business: Woodsafe Timber Protection AB with place of manufacture, Fågelbacken brandövningsplats, 72595 Västerås, Sverige.
VAT: SE556630532101
Phone: 010-206 72 30. Technical support 010-206 72 37.
E-mail: kundtjanst@woodsafes.com
Website: www.woodsafes.com
Registered trademark: WOODSAFE® Exterior WFX™

5. System for assessment and continuous control of the construction product's performance, system 1

System 1 for reaction to fire and system 4 for other properties. Production is carried out, controlled and operated by the quality system WQS (Woodsafe Quality System). The quality system ensures that the performance of the manufactured products complies with the characteristics declared in this performance declaration.

6. Declared performance in accordance with harmonized standard and notified body

Fire classification

- EN13501-1

Harmonized product standard wood panels

- EN14915:2013



Control body for continuous manufacturing control

- RISE No.0402 Control agreement number 210-09-0082, Rev. 2024-04-11
- Control of continuity of product performance according to system 1 and has issued attestation of continuity of product performance.

WOODSAFE®

2.19 Declaration of Performance Woodsafe WFX Heat modified Poplar panel Saicos oil

7. Stated performance

Essential properties	Performance			
Reaction to fire	Fire class	B-s1,d0 at 18(9)mm thickness. B-s2,d0 at >18(9)mm thickness Classified according to EN13501-1		
	Joints	Horizontal and vertical		
	Installation (1,2,3,4)	1 – Assembly: Horizontal – OK Vertical - OK Mechanically attached 2 – With an air gap to the substrate 3 – Insulation Kingspan Kooltherm K15C with 100 mm thickness 4 – NPD		
		Horizontal installation	Vertical installation	
				
	Battens (2)	Fire impregnated wooden battens ≥ 46mm thickness		
Substrate (3)	Density	Minimum thickness	Fire class EN13501-1	Fire class for wood-based substrates EN13501-1
	Ca 35 kg/m3	100mm	C-s2,d0	-
Release of formaldehyde	NPD			
Pentachlorophenol content	None			
Vapor permeability	NPD			
Sound absorption	NPD			

Use class	Area of use			Additional information
EN16755	INT1 <i>Normal dry interior</i>	INT2 <i>Varying moist interior</i>	EXT <i>Damp interior and exterior environment</i>	The fire retardant is approved for exterior exposure without surface treatment requirements. Can also be used in an interior environment. Approval is confirmed in a separate type approval certificate.

Intended use	Exterior
Panel type	Fire protection impregnated heat modified cladding
Wood specie	Poulus (Poplar)
Density	390-490 kg/m3
Fastening	Stainless acid-resistant screw or nail A4

8. REACH: SVHC (Substances of Very High Concern)

WOODSAFE®


2.19 Declaration of Performance Woodsafe WFX Heat modified Poplar panel Saicos oil

WOODSAFE® Exterior WFX consistent with both REACH Regulation (EC) 1907/2006 and the Biocidal Products Regulation (EU) 528/2012. Exterior WFX does not contain any prohibited chemicals according to REACH. Some substances may be on the SVHC list according to CLP regulations, but as a final product and using fire retardant treated wood, Woodsafe Exterior WFX is not classified as hazardous to health or the environment.

9. Associated instructions

Associated documents for the product are available at www.woodsafes.com/en/document-library

Västerås 2025-02-18
Woodsafe Timber Protection AB



Thomas Bengtsson, CEO

WOODSAFE®